

Modular LED Floodlight



Features

- ◆ Solid-State life/Patent high flux LEDs are used
- ◆ High reliability efficiency driver with UL/CE certified
- ◆ Efficient thermal management
- ◆ Unique optical lens design enable excellent efficacy and uniformity
- ◆ Flexible mounting hardware design suitable for various mounting
- ◆ Better CRI than HID, increasing visibility
- ◆ IP66 ingress rating suitable for outdoor use
- ◆ RoHS and CE compliant

General Specification

Input Voltage Range	100-277Vac
Input Frequency	50/60Hz
Power Factor	> 0.9
Total Harmonic Distortion	< 20%
Color Temperature	5000K, Other color temperatures are optional
Ingress Protection Rating	IP66
Surge Protection	>4KV
Operating Temperature Range	-40°C to 50°C



Model Specification

Model Number	Power Consumption (W)	Luminous Flux (lm)	Module Number	Weight (KG)
TTL-0704-01	40	4,400	1	2.4
TTL-1508-01	80	8,800	2	4.0
TTL-2512-01	120	13,500	3	6.5
TTL-4015-01	150	16,500	3	6.5
TTL-4020-01	200	22,000	4	7.1
TTL-4024-01	240	26,500	6	10.0
TTL-4030-01	300	33,000	6	10.0

Light Distribution

